



EL-2632e SCISSOR



EL SERIES

SELF-PROPELLED MOBILE ELEVATED WORK PLATFORM

STANDARD FEATURES

- ▶ Electric drive
- ▶ Proportional controls
- ▶ LeakGuard®
- ▶ 110V power-to-platform
- ▶ Indoor & outdoor operation settings
- ▶ 30A charger
- ▶ Non-slip deck
- ▶ All motion alarm
- ▶ Flashing beacon
- ▶ Removable platform controls
- ▶ Self-locking gate
- ▶ Lifiable with forklift or crane
- ▶ Dual maintenance bars
- ▶ Onboard diagnostic system
- ▶ Manual decent cable
- ▶ Active tilt alarm
- ▶ Slide out extension
- ▶ Automatic pothole protection
- ▶ Non-marking tires
- ▶ Horn
- ▶ CAN communication protocol
- ▶ 2-year parts & labor warranty
- ▶ 5-year structural warranty

STANDARDS COMPLIANCE

- ▶ ANSI A92.20

OPTIONS

- ▶ Perimeter Lights
- ▶ Telematics

EL SERIES

SPECIFICATIONS		EL-2632e
A	Working Height (2 Person Indoor)	32.3 ft 9.85 m
	Working Height (1 Person Outdoor)	26 ft 7.9 m
B	Platform Height Maximum (2 Person Indoor)	26.3 ft 8 m
	Platform Height Maximum (1 Person Outdoor)	20 ft 6.1 m
C	Platform Height Minimum	47.6 in 1.21 m
D	Ground Clearance Elevated	0.79 in 2 cm
E	Ground Clearance Lowered	3.5 in 9 cm
F	Overall Length w/ Step	97.3 in 2.47 m
G	Overall Width	31.5 in 0.8 m
H	Stowed Height (Rails Unfolded)	91 in 2.31 m
	Stowed Height (Rails Folded)	71 in 1.8 m
I	Platform Length	91 in 2.31 m
J	Platform Width	31 in 0.79 m
	Slide Out Extension Deck Length	34 in 0.86 m
	Wheelbase	73.2 in 1.86 m
	Tires	15 x 5 in 38 x 12.7 cm

PERFORMANCE	
Rated Occupancy (Indoor/Outdoor)	2 / 1 Person(s)
Platform Capacity	530 lbs 240 kg
Slide Out Extension Deck Capacity	250 lbs 113 kg
Gradeability	25%
Inside Turn Radius	0 in 0 cm
Drive Speed Elevated	0.4 mph 0.6 km/h
Drive Speed Lowered	2.8 mph 4.5 km/h
Working Slope	1.5° / 3°
Lift Speed (Up/Down)	44 / 38 s
Weight	5220 lbs 2368 kg
POWER	
Hydraulic Tank Capacity	5.5 gal 20.7 L
Battery	4 x 6V 225 Ah

